

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

COMPONENT FOR THE ROTOR OR STATOR OF AN ELECTRICAL MACHINE

Veröffentlichungsnr. (Sek.) ☐ WO02058210

Veröffentlichungsdatum : 2002-07-25

Erfinder : HEIDRICH MARKUS (DE); SCHMIDT RALF (DE)

Anmelder : BOSCH GMBH ROBERT (DE); HEIDRICH MARKUS (DE); SCHMIDT RALF (DE)

Veröffentlichungsnummer : ☐ DE10106717

Aktenzeichen:(EPIDOS-INPADOC-normiert) WO2001DE04475 20011129

Prioritätsaktenzeichen:(EPIDOS-INPADOC-normiert) DE20011002011 20010118; DE20011006717 20010214

Klassifikationssymbol (IPC) : H02K1/14; H02K1/24

Klassifikationssymbol (EC) : H02K1/14D, H02K1/24

Korrespondierende Patentschriften ☐ EP1354391 (WO02058210)

Cited patent(s): GB1212451; EP1020975; JP60187247

Bibliographische Daten

According to the invention, a component (1) comprises at least two support bodies (3, 5) with pole teeth (11), whereby the separation between directly adjacent pole teeth (11) of the individual support body is sufficiently large that the winding process or the mounting of a coil is significantly simplified and an optimal filling between the pole teeth (11) is achieved.

Daten aus der **esp@cenet** Datenbank - - I2